

X50 AD

Ergonomical baling

The X50 AD is designed for users, who demand a high quality machine with focus on reliability, superior press force, and a safe, functional working environment for the operator.

The door to the chamber opens automatically, giving a rational and quick filling of waste, and the horizontal handle provides an ergonomical working posture for the operator.



1.

- **Automatic opening**

Of the automatic door

- **Easy installation**

With a low overall height

- **Safe and steady opening of door**

Operated by a strong threaded spindle



2.



3.



Technical specifications

| | |
|----------------------------|--------------------|
| Press force (t) | 50 |
| Power supply | 3x400V 50Hz 32A |
| Motor (kW) | 5.5 |
| Noise level (dB) | 71 |
| Cycle time (sec) | 23 |
| Dimensions WxDxH (mm) | 1945 x 1520 x 2580 |
| Weight (kg) | 2590 |
| Filling opening WxH (mm) | 1090 x 600 |
| Filling height (mm) | 1250 |
| Chamber height (mm) | 1700 |
| Stroke (mm) | 1210 |
| Bale size WxDxH (mm) | 1200 x 800 x 1100 |
| Bale weight cardboard (kg) | 400-450 |
| Bale weight plastic (kg) | 450-550 |



The door to the chamber opens automatically and remains down, giving rational waste filling.



With the automatic door you obtain an ergonomical working posture.

Bramidan A/S

Industrivej 69
DK-6740 Bramming
Tel. +45 7517 3266
Fax +45 7571 3177
bramidan@bramidan.dk